PANZERI

Manhattan

24V DC
XG2044-50TRACK

white

INDIRECT LIGHT

Data sheet

CODE	XG2044-50TRACK
SYSTEM POWER CONSUMPTION	max 35W/m
LIGHT SOURCE	LED
LIGHT DISTRIBUTION	diffused
POWER SUPPLY	24V DC
DRIVER	remote not included
WEIGHT	0,69 Kg
PROTECTION DEGREE	IP20
PACKING DIMENSIONS	10,5 x 54,0 x 10,5 cm
L (mm)	420
L (in)	16 5/9"
ADVISED BRACKETS	2
HOLE (mm)	425 x 58
HOLE (in)	16 3/4" x 2 2/7"

Modular profile for ceiling or wall built-in installation for interiors, with indirect light emission.
Total built-in structure in plasterboard, in extruded aluminium in RAL 9003 white powder paint.
Extruded aluminium heat sink.
Extruded polycarbonate diffuser with opaline finish.
Light modules and driver to be ordered separately.
Fastening, joining and closing accessories to be ordered separately.
Built-in hole dimension: 425x58mm (16,7x2,3")

Technical drawing



Application

Polar diagram



PANZERI

Manhattan

Accessories / source

XM1ROW HD/5MT	Strip LED, 5000mm (197") 168 LED/m 17W/m 24V DC 3000K Ra>80 1964lm/m, to be cut each 42mm (1,7").	
XM1ROW HD/5MT/2700K	Strip LED, 5000mm (197") 168 LED/m 17W/m 24V DC 2700K Ra>80 1964lm/m, to be cut each 42mm (1,7").	
XM1ROW HD/5MT/4000K	Strip LED, 5000mm (197") 168 LED/m 17W/m 24V DC 4000K Ra>80 1964lm/m, to be cut each 42mm (1,7").	
XM1ROW HF/5MT/2700K	Strip LED, 5000mm (197") 168 LED/m 10W/m 24V DC 2700K Ra>80 1200lm/m, to be cut each 42mm (1,7").	
XM1ROW HF/5MT/3000K	Strip LED, 5000mm (197") 168 LED/m 10W/m 24V DC 3000K Ra>80 1200lm/m, to be cut each 42mm (1,7").	
XM1ROW HF/5MT/4000K	Strip LED, 5000mm (197") 168 LED/m 10W/m 24V DC 4000K Ra>80 1200lm/m, to be cut each 42mm (1,7").	
YLR001.022.0110	Strip LED, 5000mm (196,9") 160 LED/m 21,6W/m 24V DC 3000K Ra>80 3020lm/m, to be cut each 50mm (2").	

Manhattan

Accessories / power supply

XM100/24 DIM

LED driver, 100W 24V DC, DALI/Push DIM dimmable.



XM120/24E

LED driver, 120W 24V DC.



XM150/24 DIM

LED driver, 150W 24V DC, DALI/Push DIM dimmable.

XM18/24 DIM

LED driver, 18W 24V DC, DALI/Push DIM dimmable.

XM180/24E

LED driver, 180W 24V DC.



XM2044-TA

Power compartment with screws for installation on junctions.



XM30/24E

LED driver, 30W 24V DC.

XM35/24 DIM

LED driver, 35W 24V DC, DALI/Push DIM dimmable.

XM6-20 UNI

LED driver, 4÷20W 250÷700mA.



Manhattan

Accessories / power supply

XM60/24 DIM

LED driver, 60W 24V DC, DALI/Push DIM dimmable.



XM60/24E

LED driver, 60W 24V DC.



PANZERI

Manhattan

Accessories / fixing

XM2044-F

Drywall fixing bracket kit.



XM2044-FP

Flush wall fixing bracket kit.



XM2044-P

Plate for hanging.



Manhattan

Accessories / junction

XM2044-ANG 3

Connection joint for two lines of modular profiles with internal perpendicular junction 90°, for total built-in installation.



XM2044-ANG 4

Connection joint for two lines of modular profiles with external perpendicular junction 90°, for total built-in installation.



XM2044-U

Linear junction kit.

XM2044-U90 1

Connection joint for two lines of modular profiles with external level junction 90°, for total built-in installation.



XM2044-U90 2

Connection joint for two lines of modular profiles with internal level junction 90°, for total built-in installation.



PANZERI

Manhattan

Accessories / closing

XM2044-T

Pair of end caps with screws.