PANZERI

East

220-240V AC
XGQ0998

plaster

DIRECT LIGHT

Data sheet

CODE	XGQ0998
SYSTEM POWER CONSUMPTION	max 50W
LIGHT SOURCE	LED retrofit / halogen
LIGHT SOURCE KIT	not included
POWER SUPPLY	220-240V AC
FREQUENCY	50/60Hz
WEIGHT	0,17 Kg
PROTECTION DEGREE	IP20
PACKING DIMENSIONS	7,5 x 10,0 x 10,0 cm

Lighting fixture for ceiling or wall built-in installation for interiors, with direct light emission.
Total built-in plaster structure for masonry or plasterboard.
Light source retaining spring clip in stainless steel.
Fixing brackets in micro-perforated sheet metal.
Recessed housing for masonry in galvanized sheet metal to be ordered separately.
Built-in hole dimension: 88x88mm (3,5x3,5")

Technical drawing



Application

PANZERI

East

Accessories / source

YLL001.050.2201 PAR16 LED lamp GU10 7,5W 220-240V AC 3000K Ra>80 680lm 60°, not dimmable.

YLS001.050.1715 LED lamp 8,5W 250mA 35V 2700K Ra>90 806lm 35°.

YLS001.050.2515 LED lamp 8,5W 250mA 35V 3000K Ra>90 854lm 35°.

YLS001.050.2915 LED lamp 8,5W 250mA 35V 4000K Ra>90 1053lm 35°.

East

Accessories / power supply

XM6-20 D/P MULTI

LED driver, 9,2÷20,4W 200÷900mA, 1-10V/DALI/Push DIM dimmable.



XM6-25 D/P MULTI

LED driver, 8,4÷25,6W 150÷900mA, DALI/Push DIM dimmable.



XM6/250/10

LED driver, 10W 250mA.



East

Accessories / connection

XM2 GU5,3 lampholder, cable and terminal block kit.

PANZERI

East

Accessories / fixing

XM0998 Galvanized sheet housing to be recessed in brick wall or concrete.