PANZERI

Roy

350/500mA DC
XR255-43-3K

white

DIRECT LIGHT

Data sheet

CODE	XR255-43-3K
SYSTEM POWER CONSUMPTION	12W/18W
EFFICACY	126.08lm/W
LIGHT SOURCE	LED
LIGHT SOURCE LIFETIME	L80 (B10) 50.000h
COLOUR TEMPERATURE	3000K Ra>85
LIGHT DISTRIBUTION	wide flood
BEAM ANGLE	55°
POWER SUPPLY	350/500mA DC
DRIVER	remote not included
NOMINAL LUMINOUS FLUX	1700lm/2350lm
LUMEN OUTPUT	1513lm/2092lm
EFFICIENCY	89%
GLARE RATING	UGR < 19
WEIGHT	0,59 Kg
PROTECTION DEGREE	IP43 IP20
SHOCK RESISTANCE RATING	IK08
GLOW WIRE TEST PERFORMANCE	850°
PACKING DIMENSIONS	135,5 x 109,0 x 129,5 cm

Technical drawing



Application

Polar diagram



PANZERI

Roy

Accessories / power supply

XM6-20 D/P MULTI

LED driver, 9,2÷20,4W 200÷900mA, 1-10V/DALI/Push DIM dimmable.



XM6-20 UNI

LED driver, 4÷20W 250÷700mA.



XM6-25 D/P MULTI

LED driver, 8,4÷25,6W 150÷900mA, DALI/Push DIM dimmable.



PANZERI

Roy

Accessories / diffusion

XMR1

Narrow beam optic.



XMR2

Flood optic.



XMR4

Diffused beam optic.